

- Full frontal visibility, even while loaded, with the unique overhead lift arm.
- Reach forks out up to four feet without repositioning the machine.
- Lift up and over, tilt and reach down simultaneously with dual joystick controls.
- Heavy-duty, solid steel frame design keeps loads stable in full turns, without added counterweight.
- Lift and carry loads on uneven ground with hydraulic frame sway control.
- Stay up and running for years with superior engineering and service.



If it were any tougher, it couldn't be built.

PETTIBONE

1100 Superior Avenue, Baraga, MI 49908
 800.GO.PETTIBONE
 gopettibone.com



PETTIBONE

Cary-Lift®

Precise hydraulics and full frontal visibility makes easy work of your toughest loads.

Safely load and unload your heaviest materials, even from rail cars, with only one operator.

MAXIMUM LOAD-HANDLING EFFICIENCY

- Overhead lift arm provides maximum visibility, when lifting, placing or transporting loads
- Standard right- and left-hand joystick controls

POWERFUL, VERSATILE MANEUVERABILITY

- Maintains maximum lift capacity in a full turn
- 90-degree fork tilt down, forward reach, hydraulic frame sway control and side shift for unmatched load manipulation
- Two-wheel, four-wheel and crab steering

PEAK PERFORMANCE IN ALL CONDITIONS

- Cummins emissions-certified engine with full electronic control protection
- Heavy-duty axles with four-wheel drive, four-wheel steer and external dry disc brakes
- Large fuel tank runs for a full workday

GREATER OPERATING COMFORT AND SAFETY

- Fully adjustable suspension seat with lumbar support
- Tilt telescopic steering column
- Full instrumentation for real-time status of all systems
- Sliding cab door with steps and hand holds

OPTIONAL ATTACHMENTS FOR EVERY JOB

- Fork frames
- Pipe and pole balers
- Log balers
- Scrap balers
- Rotating pipe and pole handlers
- Tire handlers
- Clams
- Additional attachments and lift heights available



Cary-Lift 104

Maximum lift capacity (retracted at 24" LC)	10,000 lbs. (4,536 kg)
Maximum lift height	14' (4.3 m)
Forward reach	4' (1.2 m)
Operating weight ^A	28,000 lbs. (12,701 kg)

Cary-Lift 154

Maximum lift capacity (retracted at 24" LC)	15,000 lbs. (6,804 kg)
Maximum lift height	14' (4.3 m)
Forward reach	4' (1.2 m)
Operating weight ^A	42,200 lbs. (19,142 kg)

Cary-Lift 204

Maximum lift capacity (retracted at 24" LC)	20,000 lbs. (9,072 kg)
Maximum lift height	14' (4.3 m)
Forward reach	4' (1.2 m)
Operating weight ^A	45,000 lbs. (20,412 kg)

Cary-Lift 254

Maximum lift capacity (retracted at 24" LC)	25,000 lbs. (11,340 kg)
Maximum lift height	14' (4.3 m)
Forward reach	4' (1.2 m)
Operating weight ^A	53,300 lbs. (24,176 kg)

Cary-Lift 304

Maximum lift capacity (retracted at 36" LC)	30,000 lbs. (13,608 kg)
Maximum lift height	14' (4.3 m)
Forward reach	4' (1.2 m)
Operating weight ^A	77,860 lbs. (35,317 kg)

^A Approximate